



C 150 -xxxxyyyyy

xxxx 12-24V  
yyyyy 1mA-1250mA

**Features**

- 12-24V DC Input
- Single Output to 150W Max
- 5 Years Warranty



Model	O/P Voltage	O/P Current	Watt
C150-120001250	12V	12.5A	150W
C150-190007890	19V	7.89A	150W
C150-240006250	24V	6.25A	150W

**Input**

Rated Input Voltage	12-24V DC
Rated Input Current	14A Max input Current

**Output**

Power	150W Max
Load Regulation	±5%

**Protection**

Over Voltage Protection	Auto recovery
Short Circuit Protection	Auto recovery
Over Current Protection	Auto recovery

**Safety Approvals**

CE FCC UKCA PSE

**Safety Standards**

EMI STANDARD EN50498:2010, BS EN 50498: 2010, J55032(H29)  
FCC 47 CFR Part 15 Subpart B,ANSI C63.4-2014

**Mechanicals**

Case Dimension L91.1 x W37.9 x H28mm  
Cable UL20276 # 18AWG , 1800mm ± 30  
Case Material UL94-V1

**Environmental**

Operation Temperature	-10 °C – 40 °C
Storage Temperature	-25 °C – 70 °C
Operation Humidity	5%( 0°C) ~ 90%( 40°C)
Storage Humidity	5%~ 95%